
dalmec

Industrial Manipulators



WEIGHT CAPACITY **140 Kg**

RADIUS **5000 mm**

PRESSURE **0.7-0.8 Mpa**

VERTICAL LIFT **1800 mm**


VERSIONS
- COLUMN
- FIXED OVERHEAD
- RUNNING OVERHEAD


Pneumatic Manipulator **POSIFIL PF** with double cable

POSIFIL PF, equipped with special gripping tools, allows to handle loads in a weightless condition in any direction. The gripping tool is connected to the balancing group through two single steel cables to guarantee max safety. The particular double arm structure and middle joint makes it easy to operate within the entire working area.

POSIFIL® PF


Posifil column mounted - PFC






Structural versions: column mounted on fixed base-plate, autostable base-plate of our supply properly dimensioned.

Posifil overhead mounted - PFF





	Mounting flange ø 70	Mounting flange ø 95
No. holes	4	6
ø E	200 mm	250 mm
ø holes	18 mm	20 mm



Configuration and measurements may change upon the Customer's specific requirements

Posifil overhead trolley mounted - PFS





Air supply: Dry and oil-free compressed air min constant 0.7÷0.8 MPa

Copyright © 2017 by Dalmec S.p.A Technical data and measures are indicative only and not binding. Dalmec reserves the right to make changes, at any time without notice.